

SAFETY DATA SHEET

Subli Glaze Translucent White Coating DC-TW400 400ml Aerosols

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name Subli Glaze Translucent White Coating DC-TW400 400ml Aerosols 1812

Product number

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Paint.

1.3. Details of the supplier of the safety data sheet

Supplier

Sole Juice Ltd. Unit 15 Aspen Court, Centurion
Business Park, Bessemer Way, Rotherham,
United Kingdom, S60 1FB.
www.subliglaze.com
+44 (0)1709 296 366
+44 (0)1709 718 661
info@SoleJuice.com
S60 1FB

1.4. Emergency telephone number

Emergency telephone (+44) 1709 296 366 (Hours 09:00 - 17:00 Mon to Fri)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (EC 1272/2008)

Physical hazards Aerosol 1 - H222, H229

Health hazards Eye Irrit. 2 - H319 STOT SE 3 - H336

Environmental hazards Not Classified

Classification (67/548/EEC or 1999/45/EC) F+; R12. Xi; R36. R66, R67

Human health Vapours and spray/mists in high concentrations are narcotic. See Section 11 for additional information on health hazards.

Environmental The product is not expected to be hazardous to the environment.

Physicochemical Containers can burst violently or explode when heated, due to excessive pressure build-up. The product is extremely flammable. Vapours may form explosive mixtures with air.

2.2. Label elements

Pictogram



Signal word

Danger

Hazard statements

H222 Extremely flammable aerosol.
H229 Pressurised container: may burst if heated
H319 Causes serious eye irritation.
H336 May cause drowsiness or dizziness.

Sole Juice Limited - Subli Glaze Translucent White Coating DC-TW400 400ml Aerosols

Precautionary statements	<p>P102 Keep out of reach of children.</p> <p>P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.</p> <p>P211 Do not spray on an open flame or other ignition source.</p> <p>P251 Do not pierce or burn, even after use.</p> <p>P261 Avoid breathing vapour/ spray.</p> <p>P271 Use only outdoors or in a well-ventilated area.</p> <p>P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.</p> <p>P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.</p> <p>P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.</p> <p>P312 Call a POISON CENTER/ doctor if you feel unwell.</p> <p>P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.</p>
Supplemental label information	EUH066 Repeated exposure may cause skin dryness or cracking.
Contains	ACETONE, N-BUTYL ACETATE, NAPHTHA (PETROLEUM), HYDROTREATED HEAVY, BUTANONE, ISOPROPANOL
Supplementary precautionary statements	<p>P264 Wash contaminated skin thoroughly after handling.</p> <p>P337+P313 If eye irritation persists: Get medical advice/ attention.</p> <p>P403+P233 Store in a well-ventilated place. Keep container tightly closed.</p> <p>P405 Store locked up.</p> <p>P501 Dispose of contents/ container in accordance with national regulations.</p>

2.3. Other hazards

This product does not contain any substances classified as PBT or vPvB.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

DIMETHYL ETHER		30-60%
CAS number: 115-10-6	EC number: 204-065-8	
Classification		
Flam. Gas 1 - H220		
Press. Gas, Liquefied - H280		
ACETONE		30-60%
CAS number: 67-64-1	EC number: 200-662-2	REACH registration number: 01-2119471330-49-XXXX
Classification		
Flam. Liq. 2 - H225		
Eye Irrit. 2 - H319		
STOT SE 3 - H336		

Sole Juice Limited - Subli Glaze Translucent White Coating DC-TW400 400ml Aerosols

N-BUTYL ACETATE		5-10%
CAS number: 123-86-4	EC number: 204-658-1	REACH registration number: 01-2119485493-29-XXXX
Classification		
Flam. Liq. 3 - H226 STOT SE 3 - H336		
BUTANONE		1-5%
CAS number: 78-93-3	EC number: 201-159-0	REACH registration number: 01-2119457290-43-XXXX
Classification		
Flam. Liq. 2 - H225 Eye Irrit. 2 - H319 STOT SE 3 - H336		
2-(2-BUTOXYETHOXY)ETHANOL		1-5%
CAS number: 112-34-5	EC number: 203-961-6	REACH registration number: 01-2119475104-44-XXXX
Classification		
Eye Irrit. 2 - H319		
Titanium Dioxide		1-5%
CAS number: 13463-67-7		
Classification		
Not Classified		
PROPAN-2-OL		1-5%
CAS number: 67-63-0	EC number: 200-661-7	REACH registration number: 01-2119457558-25-XXXX
Classification		
Flam. Liq. 2 - H225 Eye Irrit. 2 - H319 STOT SE 3 - H336		

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. Get medical attention if any discomfort continues.

Inhalation

Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. If in doubt, get medical attention promptly.

Sole Juice Limited - Subli Glaze Translucent White Coating DC-TW400 400ml Aerosols

Ingestion	Rinse mouth thoroughly with water. Remove person to fresh air and keep comfortable for breathing. Get medical attention.
Skin contact	Wash skin thoroughly with soap and water. Get medical attention promptly if symptoms occur after washing.
Eye contact	Remove any contact lenses and open eyelids wide apart. Rinse immediately with plenty of water. Continue to rinse for at least 15 minutes. Get medical attention promptly if symptoms occur after washing.
Protection of first aiders	First aid personnel should wear appropriate protective equipment during any rescue.

4.2. Most important symptoms and effects, both acute and delayed

General information See Section 11 for additional information on health hazards.

4.3. Indication of any immediate medical attention and special treatment needed

Notes for the doctor Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media Foam, carbon dioxide or dry powder.

5.2. Special hazards arising from the substance or mixture

Specific hazards Containers can burst violently or explode when heated, due to excessive pressure build-up.

5.3. Advice for firefighters

Protective actions during firefighting Use water to keep fire exposed containers cool and disperse vapours. Cool containers exposed to heat with water spray and remove them from the fire area if it can be done without risk.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions Avoid inhalation of vapours and contact with skin and eyes. Ensure suitable respiratory protection is worn during removal of spillages in confined areas.

6.2. Environmental precautions

Environmental precautions Avoid discharge into drains.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up Eliminate all sources of ignition. No smoking, sparks, flames or other sources of ignition near spillage. Provide adequate ventilation. Absorb in vermiculite, dry sand or earth and place into containers.

6.4. Reference to other sections

Reference to other sections For personal protection, see Section 8. See Section 11 for additional information on health hazards. See Section 12 for additional information on ecological hazards. For waste disposal, see Section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Usage precautions Keep away from heat, sparks and open flame. Read and follow manufacturer's recommendations. When sprayed on a naked flame or any incandescent material the aerosol vapours can be ignited. Use suitable respiratory protection if ventilation is inadequate.

Sole Juice Limited - Subli Glaze Translucent White Coating DC-TW400 400ml Aerosols

Advice on general occupational hygiene Wash promptly with soap and water if skin becomes contaminated. Do not eat, drink or smoke when using this product.

7.2. Conditions for safe storage, including any incompatibilities

Storage precautions Protect from freezing and direct sunlight. Store in a dry place. Do not store near heat sources or expose to high temperatures. Keep away from heat, sparks and open flame.

7.3. Specific end use(s)

Specific end use(s) The identified uses for this product are detailed in Section 1.2.

SECTION 8: Exposure Controls/personal protection

8.1. Control parameters

Occupational exposure limits

DIMETHYL ETHER

Long-term exposure limit (8-hour TWA): 400 ppm

Short-term exposure limit (15-minute): 500 ppm

ACETONE

Long-term exposure limit (8-hour TWA): WEL 500 ppm 1210 mg/m³

Short-term exposure limit (15-minute): WEL 1500 ppm 3620 mg/m³

N-BUTYL ACETATE

Short-term exposure limit (15-minute): WEL 966 mg/m³ 200 ppm

Long-term exposure limit (8-hour TWA): WEL 724 mg/m³ 150 ppm

BUTANONE

Short-term exposure limit (15-minute): WEL 899 mg/m³ 300 ppm

Long-term exposure limit (8-hour TWA): WEL 600 mg/m³ 200 ppm

2-(2-BUTOXYETHOXY)ETHANOL

Long-term exposure limit (8-hour TWA): WEL 10 ppm 67.5 mg/m³

Short-term exposure limit (15-minute): WEL 15 ppm 101.2 mg/m³

Titanium Dioxide

Long-term exposure limit (8-hour TWA): WEL 10 mg/m³ inhalable dust

Long-term exposure limit (8-hour TWA): WEL 4 mg/m³ respirable dust

PROPAN-2-OL

Long-term exposure limit (8-hour TWA): WEL 400 ppm 999 mg/m³

Short-term exposure limit (15-minute): WEL 500 ppm 1250 mg/m³

WEL = Workplace Exposure Limit

DIMETHYL ETHER (CAS: 115-10-6)

DNEL Workers - Inhalation; Long term systemic effects: 1894 mg/m³
Consumer - Inhalation; Long term systemic effects: 471 mg/m³

PNEC

- Fresh water; 0.155 mg/l
- Marine water; 0.016 mg/l
- Intermittent release; 1.549 mg/l
- Sediment (Freshwater); 0.681 mg/kg
- Sediment (Marinewater); 0.069 mg/kg
- STP; 160 mg/l
- Soil; 0.045 mg/kg

ACETONE (CAS: 67-64-1)

Sole Juice Limited - Subli Glaze Translucent White Coating DC-TW400 400ml Aerosols

DNEL Workers - Dermal; Long term systemic effects: 186 mg/kg/day
 Workers - Inhalation; Short term local effects: 2420 mg/m³
 Workers - Inhalation; Long term systemic effects: 1210 mg/m³

PNEC - Sediment (Freshwater); 30.4 mg/kg
 - Sediment (Marinewater); 3.04 mg/kg
 - Marine water; 1.06 mg/l
 - Soil; 29.5 mg/kg

N-BUTYL ACETATE (CAS: 123-86-4)

DNEL Consumer - Inhalation; Short term local effects: 859.7 mg/m³
 Consumer - Inhalation; Short term systemic effects: 859.7 mg/m³
 Workers - Inhalation; Short term systemic effects: 960 mg/m³
 Workers - Inhalation; Short term local effects: 960 mg/m³
 Consumer - Inhalation; Long term local effects: 102.34 mg/m³
 Workers - Inhalation; Long term local effects: 480 mg/m³
 Consumer - Inhalation; Long term systemic effects: 102.34 mg/m³
 Workers - Inhalation; Long term systemic effects: 480 mg/m³

PNEC - Fresh water; 0.18 mg/l
 - Sediment (Freshwater); 0.981 mg/kg
 - Sediment (Marinewater); 0.981 mg/kg
 - Marine water; 0.018 mg/l
 - STP; 35.6 mg/l
 - Soil; 0.0903 mg/kg

BUTANONE (CAS: 78-93-3)

DNEL Consumer - Dermal; Long term systemic effects: 412 mg/kg/day
 Consumer - Oral; Long term systemic effects: 31 mg/kg/day
 Workers - Dermal; Long term systemic effects: 1161 mg/kg/day
 Consumer - Inhalation; Long term systemic effects: 106 mg/m³
 Workers - Inhalation; Long term systemic effects: 600 mg/m³

PNEC - Fresh water; 55.8 mg/l
 - Sediment (Freshwater); 284.7 mg/kg
 - Intermittent release; 55.8 mg/l
 - Sediment (Marinewater); 284.7 mg/kg
 - Marine water; 55.8 mg/l
 - STP; 709 mg/l
 - Soil; 22.5 mg/kg

2-(2-BUTOXYETHOXY)ETHANOL (CAS: 112-34-5)

DNEL Workers - Inhalation; Long term local effects: 7.5 mg/m³
 Workers - Dermal; Long term systemic effects: 10 mg/kg/day
 Workers - Inhalation; Long term systemic effects: 5 mg/m³
 Workers - Oral; Long term systemic effects: 1.3 mg/kg/day
 Workers - Inhalation; Short term systemic effects: 5 mg/m³
 Consumer - Inhalation; Short term local effects: 15 ppm
 Consumer - Dermal; Long term systemic effects: 20 mg/kg/day
 Consumer - Inhalation; Long term systemic effects: 10 ppm
 Consumer - Inhalation; Long term local effects: 5 ppm

Sole Juice Limited - Subli Glaze Translucent White Coating DC-TW400 400ml Aerosols

PNEC	- Fresh water; 1 mg/l
	- Sediment (Freshwater); 4 mg/kg
	- Intermittent release; 3.9 mg/l
	- Sediment (Marinewater); 0.4 mg/kg
	- Marine water; 0.1 mg/l
	- STP; 200 mg/l

PROPAN-2-OL (CAS: 67-63-0)

DNEL	Workers - Dermal; Long term systemic effects: 888 mg/kg/day
	Workers - Inhalation; Long term systemic effects: 500 mg/m ³
	Consumer - Dermal; Long term systemic effects: 319 mg/kg/day
	Consumer - Inhalation; Long term systemic effects: 89 mg/m ³
	Consumer - Oral; Long term systemic effects: 26 mg/kg/day
PNEC	- Fresh water; 140.9 mg/l
	- Marine water; 140.9 mg/l
	- Intermittent release; 140.9 mg/l
	- STP; 2251 mg/l
	- Soil; 28 mg/kg
	- Sediment; 552 mg/kg

8.2. Exposure controls

Eye/face protection	Eyewear complying with an approved standard should be worn if a risk assessment indicates eye contact is possible.
Hand protection	No specific requirements are anticipated under normal conditions of use.
Other skin and body protection	Wear suitable protective equipment for prolonged exposure and/or high concentrations of vapours, spray or mist.
Respiratory protection	No specific recommendations. If ventilation is inadequate, suitable respiratory protection must be worn.

SECTION 9: Physical and Chemical Properties

9.1. Information on basic physical and chemical properties

Appearance	Aerosol.
Colour	White.
Odour	Solvents
Odour threshold	No information available.
pH	No information available.
Melting point	No information available.
Initial boiling point and range	-25 (-25 TO 230)°C @
Flash point	-41°C CC (Closed cup).
Evaporation rate	No information available.
Evaporation factor	No information available.
Flammability (solid, gas)	No information available.
Upper/lower flammability or explosive limits	Lower flammable/explosive limit: 0.6 % Upper flammable/explosive limit: 32 %

Sole Juice Limited - Subli Glaze Translucent White Coating DC-TW400 400ml Aerosols

Vapour pressure	No information available.
Vapour density	No information available.
Relative density	0.765
Solubility(ies)	Insoluble in water.
Partition coefficient	No information available.
Auto-ignition temperature	225°C
Decomposition Temperature	No information available.
Viscosity	No information available.
Explosive properties	No information available.
Oxidising properties	No information available.

9.2. Other information

Other information	None.
-------------------	-------

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity	No test data specifically related to reactivity available for this product or its ingredients.
------------	------------------------------------------------------------------------------------------------

10.2. Chemical stability

Stability	The product may not be stable under some conditions of storage or use.
-----------	------------------------------------------------------------------------

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions	None known.
------------------------------------	-------------

10.4. Conditions to avoid

Conditions to avoid	Avoid heat, flames and other sources of ignition. Avoid exposing aerosol containers to high temperatures or direct sunlight.
---------------------	------------------------------------------------------------------------------------------------------------------------------

10.5. Incompatible materials

Materials to avoid	None known.
--------------------	-------------

10.6. Hazardous decomposition products

Hazardous decomposition products	None at ambient temperatures.
----------------------------------	-------------------------------

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity - dermal

ATE dermal (mg/kg)	28,758.16993464
--------------------	-----------------

Acute toxicity - inhalation

ATE inhalation (vapours mg/l)	287.58169935
-------------------------------	--------------

Inhalation	May cause drowsiness or dizziness. Vapours in high concentrations are narcotic. Vapours may cause headache, fatigue, dizziness and nausea.
------------	--------------------------------------------------------------------------------------------------------------------------------------------

Skin contact	Skin irritation should not occur when used as recommended.
--------------	------------------------------------------------------------

Sole Juice Limited - Subli Glaze Translucent White Coating DC-TW400 400ml Aerosols

Eye contact	Causes serious eye irritation.
Acute and chronic health hazards	No known chronic or acute health risks.
Route of entry	Inhalation Skin and/or eye contact

DIMETHYL ETHER

Acute toxicity - inhalation

Acute toxicity inhalation (LC₅₀ gases ppmV) 164,000.0

Species Rat

ATE inhalation (gases ppm) 164,000.0

ACETONE

Acute toxicity - oral

Acute toxicity oral (LD₅₀ mg/kg) 5,800.0

Species Rat

ATE oral (mg/kg) 5,800.0

Acute toxicity - dermal

Acute toxicity dermal (LD₅₀ mg/kg) 7,800.0

Species Rabbit

ATE dermal (mg/kg) 7,800.0

Acute toxicity - inhalation

Acute toxicity inhalation (LC₅₀ vapours mg/l) 21.0

Species Rat

ATE inhalation (vapours mg/l) 21.0

N-BUTYL ACETATE

Acute toxicity - oral

Acute toxicity oral (LD₅₀ mg/kg) 10,760.0

Species Rat

ATE oral (mg/kg) 10,760.0

Acute toxicity - dermal

Acute toxicity dermal (LD₅₀ mg/kg) 14,113.0

Species Rabbit

Sole Juice Limited - Subli Glaze Translucent White Coating DC-TW400 400ml Aerosols

ATE dermal (mg/kg) 14,113.0

Acute toxicity - inhalation

Acute toxicity inhalation (LC₅₀ vapours mg/l) 23.4

Species Rat

ATE inhalation (vapours mg/l) 23.4

BUTANONE

Acute toxicity - oral

Acute toxicity oral (LD₅₀ mg/kg) 2,194.0

Species Rat

ATE oral (mg/kg) 2,194.0

Acute toxicity - dermal

Acute toxicity dermal (LD₅₀ mg/kg) 5,001.0

Species Rabbit

ATE dermal (mg/kg) 5,001.0

2-(2-BUTOXYETHOXY)ETHANOL

Acute toxicity - oral

Acute toxicity oral (LD₅₀ mg/kg) 2,410.0

Species Mouse

ATE oral (mg/kg) 2,410.0

Acute toxicity - dermal

Acute toxicity dermal (LD₅₀ mg/kg) 2,764.0

Species Rabbit

ATE dermal (mg/kg) 2,764.0

PROPAN-2-OL

Acute toxicity - oral

Acute toxicity oral (LD₅₀ mg/kg) 5,045.0

Species Rat

ATE oral (mg/kg) 5,045.0

Acute toxicity - dermal

Sole Juice Limited - Subli Glaze Translucent White Coating DC-TW400 400ml Aerosols

Acute toxicity dermal (LD₅₀ 12,800.0 mg/kg)

Species Rabbit

ATE dermal (mg/kg) 12,800.0

Acute toxicity - inhalation

Acute toxicity inhalation (LC₅₀ vapours mg/l) 30.0

Species Rat

ATE inhalation (vapours mg/l) 30.0

SECTION 12: Ecological Information

12.1. Toxicity

DIMETHYL ETHER

Acute toxicity - fish LC₅₀, 96 hours: 4001 mg/l, Poecilia reticulata (Guppy)

Acute toxicity - aquatic invertebrates EC₅₀, 48 hours: 4001 mg/l, Daphnia magna

Acute toxicity - aquatic plants EC₅₀, 96 hours: 154.9 mg/l, Fish

ACETONE

Acute toxicity - fish EC₅₀, 96 hours: 8300 mg/l, Lepomis macrochirus (Bluegill)

Acute toxicity - aquatic invertebrates EC₅₀, : 8800 mg/l, Daphnia magna

N-BUTYL ACETATE

Acute toxicity - fish LC₅₀, 24 hours: 54 mg/l, Algae
LC₅₀, 96 hours: 18 mg/l, Pimephales promelas (Fat-head Minnow)

Acute toxicity - aquatic invertebrates EC₅₀, 48 hours: 44 mg/l, Daphnia magna

Acute toxicity - aquatic plants EC₅₀, 72 hours: 647.7 mg/l, Scenedesmus subspicatus

BUTANONE

Acute toxicity - fish LC₅₀, 24 hours: 5001 mg/l, Algae

Acute toxicity - aquatic plants LOEC, : 101 mg/l, Fish

2-(2-BUTOXYETHOXY)ETHANOL

Acute toxicity - fish LC₅₀, 96 hours: 1300 mg/l, Lepomis macrochirus (Bluegill)

Sole Juice Limited - Subli Glaze Translucent White Coating DC-TW400 400ml Aerosols

Acute toxicity - aquatic invertebrates	EC ₅₀ , 48 hours: 101 mg/l, Daphnia magna
Acute toxicity - aquatic plants	EC ₅₀ , 96 hours: 101 mg/l, Scenedesmus subspicatus

PROPAN-2-OL

Acute toxicity - fish	LC ₅₀ , 96 hours: 9640 mg/l, Pimephales promelas (Fat-head Minnow)
Acute toxicity - aquatic invertebrates	EC ₅₀ , 48 hours: 13299 mg/l, Daphnia magna
Acute toxicity - aquatic plants	EC ₅₀ , 72 hours: >1 mg/l, Desmodesmus subspicatus

12.2. Persistence and degradability

Persistence and degradability No data available.

12.3. Bioaccumulative potential

Partition coefficient No information available.

12.4. Mobility in soil

Mobility No data available

12.5. Results of PBT and vPvB assessment

Results of PBT and vPvB assessment This product does not contain any substances classified as PBT or vPvB.

12.6. Other adverse effects

Other adverse effects None known.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

General information	Dispose of waste product or used containers in accordance with local regulations
Disposal methods	Containers should be thoroughly emptied before disposal because of the risk of an explosion. Do not pierce or burn, even after use.

SECTION 14: Transport information

14.1. UN number

UN No. (ADR/RID)	1950
UN No. (IMDG)	1950
UN No. (ICAO)	1950
UN No. (ADN)	1950

14.2. UN proper shipping name

Proper shipping name (ADR/RID)	AEROSOLS, FLAMMABLE
Proper shipping name (IMDG)	AEROSOLS, FLAMMABLE
Proper shipping name (ICAO)	AEROSOLS, FLAMMABLE

Sole Juice Limited - Subli Glaze Translucent White Coating DC-TW400 400ml Aerosols

Proper shipping name (ADN) AEROSOLS, FLAMMABLE

14.3. Transport hazard class(es)

ADR/RID class	2.1
ADR/RID classification code	5F
ADR/RID label	2.1
IMDG class	2.1
ICAO class/division	2.1
ADN class	2.1

Transport labels



14.4. Packing group

Not applicable.

14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant

No.

14.6. Special precautions for user

EmS	F-D, S-U
ADR transport category	2
Tunnel restriction code	(D)

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Transport in bulk according to Not applicable.

Annex II of MARPOL 73/78
and the IBC Code

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations	The Aerosol Dispensers Regulations 2009 (SI 2009 No. 2824).
EU legislation	Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures (as amended). Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) (as amended). Council Directive of 20 May 1975 on the approximation of the laws of the Member States relating to aerosol dispensers (75/324/EEC) (as amended).

15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

SECTION 16: Other information

Revision date	20/01/2017
---------------	------------

Sole Juice Limited - Subli Glaze Translucent White Coating DC-TW400 400ml Aerosols

Revision	2
Supersedes date	20/08/2014
SDS number	4931
Hazard statements in full	H220 Extremely flammable gas. H222 Extremely flammable aerosol. H225 Highly flammable liquid and vapour. H226 Flammable liquid and vapour. H229 Pressurised container: may burst if heated H280 Contains gas under pressure; may explode if heated. H304 May be fatal if swallowed and enters airways. H312 Harmful in contact with skin. H315 Causes skin irritation. H319 Causes serious eye irritation. H332 Harmful if inhaled. H335 May cause respiratory irritation. H336 May cause drowsiness or dizziness. H373 May cause damage to organs through prolonged or repeated exposure.

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.